



C60

IC- PNEUMATIC LPG

13,500 / 15,500 / 16,500 / 18,000 lbs.

(6000 / 7000 / 7500 / 8000 kg)

STANDARD SPECIFICATIONS

C60/70/75/80

Manufacturer's Designation		C60D	C70D	C75D	C80D	C60L	C70L	C75L
Load Capacity / Rated Load	lbs(kg)	13,500 (6000)	15,500 (7000)	16,500 (7500)	18,000 (8000)	13,500 (6000)	15,500 (7000)	16,500 (7500)
Height Overhead Guard	in(mm)	93.3 (2370)	93.3 (2370)	93.3 (2370)	93.3 (2370)	93.3 (2370)	93.3 (2370)	93.3 (2370)
Width	in(mm)	83.7 (2125)	83.7 (2125)	83.7 (2125)	83.7 (2125)	83.7 (2125)	83.7 (2125)	83.7 (2125)
Right Angle Stack (add load length & clearance)	in(mm)	158.9 (4037)	160.1 (4067)	160.1 (4067)	172.9 (4392)	158.9 (4037)	160.1 (4067)	160.1 (4067)
Outside Turning Radius	in(mm)	134.6 (3420)	135.8 (3450)	135.8 (3450)	148.6 (3375)	134.6 (3450)	135.8 (3450)	135.8 (3450)
Travel Speed Loaded / Unloaded	mph (kph)	18.8/20.4 (30.4/32.9)	18.7/20.4 (30.2/32.9)	18.1/17.5 (29.2/32.8)	18.4/20.3 (29.7/32.7)	18.2/19.5 (29.3/31.4)	18.0/18.7 (29/30.2)	17.5/18.4 (28.3/29.6)
Power Unit	HP(KW) @ rpm	Deutz TD3.6 74.3 (55.4) @ 2300	Deutz TD3.6 74.3 (55.4) @ 2300	Deutz TD3.6 74.3 (55.4) @ 2300	Deutz TD3.6 74.3 (55.4) @ 2300	PSI-4X 110 (82) @ 2400	PSI-4X 110 (82) @ 2400	PSI-4X 110 (82) @ 2400

STANDARD FEATURES

- Deutz TD3.6 Diesel Engine • EPA Compliant • Standard and Triple Uprights • Full Range of Lift Heights
- High Visibility "Silent Staging" Uprights • Three Speed Auto-Shift Transmission • Wet Disc Brakes
- Planetary Drive Axle • Square Fin Radiator • High Capacity Cooling System • Hood Mounted Control Levers
- LCD Display • Power Steering • Tilt Steering Wheel • Traction Disable Seat Switch • Operator Presence System • Pre-Cleaner • Rear Combination Lights with Turn Signals • Full Suspension Vinyl Seat • Orange Seatbelt



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com